



Groot-Bijgaardenstraat 124  
B-1620 Drogenbos

## Material : Nitrile Butadiene Rubber

Suebel Code : NT4B FG      Colour : GREEN

### Grade : Rubber for Food Contact Applications.

- 1) *Our Food Grade Compounds were successfully tested at IRMRA [A NABL(ISO-17025-2005) Accredited Laboratory referring to **US-FDA-177-2600.Clause(F)**.*
- 2) *All ingredients used in forming the compounds are from the reputed suppliers & food grade certified.*

Revision date : 01/10/2011

Physical properties	nominal	actual	units
As per BS 5176, Grade-I			
<b>Hardness</b>			
BS 903 A 26, 23 °C	70-75	72	Shore A
<b>Tensile strength</b>			
BS 903 A 2, 23 °C	> 102	158	Kg/Cm <sup>2</sup>
<b>Elongation at break</b>			
BS 903 A 2, 23 °C	> 250	450	%
<b>Compression set</b>			
BS 903 A 6, 100 °C, 22 h, 25 %	< 50	32	%
<b>Air Ageing</b>			
BS 903 A 19, 100 °C, 70 h			
<b>Hardness Change</b>	<(±15)	4	Points
<b>Tensile Change</b>	<(±30)	-14.5	%
<b>Elongation Change</b>	<(-50)	-17.7	%
<b>Fluid Resistance, ASTM Oil-3</b>			
BS 903 A 16, 100 °C, 70 h			
<b>Volume Change</b>	-0 to +40	18	%
<b>Specific Gravity</b>			
BS 903 A 1, 23 °C	---	1.22	Gm/cc
<b>Ash Content</b>			
800°C, 2 Hrs	---	7.58	%

RC Bruxelles 543672  
TVA : BE 443 660 083  
Fortis Bank

Tel : 00 32 2 – 331 25 32  
Fax : 00 32 2 – 378 15 16  
IBAN : BB88 2100 9023 8041

Web : [www.suebel.be](http://www.suebel.be)  
Email : [sales@suebel.be](mailto:sales@suebel.be)  
Swift (BIC) : GEBABEBB